



## DATA SHEET NO. 3300-910

# SPECTRUM 910 Liquid Stamp Protectant “Cherry Blast”

### DESCRIPTION

SPECTRUM 910 liquid stamp protectant is a blend of natural and synthetic chemicals that protects decorative concrete texturing tools from the alkaline concrete surface. Working with SPECTRUM 910 is more tolerable to applicators, due to the refreshing “cherry blast” scent that accompanies its application.

### USES

SPECTRUM 910 is ideal for use on fresh concrete surfaces where no secondary colour is required. SPECTRUM 910 can be used on polyurethane, metal, fiberglass, and rubber decorative concrete tools for efficient protection from fresh concrete surfaces.

### FEATURES/BENEFITS

- Minimizes wear and tear to decorative concrete tools.
- Is a clear liquid and will not affect the final appearance of a concrete project.
- Can also be used in combination with SPECTRUM 930 patina acid stain and various sealers from W. R. MEADOWS.
- Allows for the surface to be reworked if needed ... simply trowel surface smooth, reapply SPECTRUM 910, and re-stamp.

### PACKAGING

18.9 Litre (5 U.S. Gal.) Pails

### COVERAGE

6.1 - 8.6 m<sup>2</sup>/L (250 - 350 ft.<sup>2</sup>/U.S. gal.)

### SHELF LIFE

When stored indoors and in original, unopened containers at temperatures between 4° - 32° C, shelf life is two years from date of manufacture.

### APPLICATION

**Surface Preparation ...** Clean existing debris from all stamping tools. Ensure that concrete is sufficiently set and that all bleed water has dissipated from concrete surface. Concrete surface should also be at a stage where it is able to support the load of workers as well as any tools that are required.

**Application Method ...** Liberally apply SPECTRUM 910 by commercial sprayer (such as a Chapin 19069) with a 1.9 LPM nozzle to the decorative concrete tools and to the concrete surface. Ensure that the surface is uniformly covered. SPECTRUM 910 stamp protectant should not be applied too far in advance, as evaporation of the product may occur.

**NOTE:** SPECTRUM 910 liquid stamp protectant should be applied in a clean, even mist in order to prevent spotting. Place the decorative concrete texturing or stamping mats over the area that has been covered with SPECTRUM 910. Using an impact tool, ensure that the concrete surface is adequately stamped for depth of texture. Remove the decorative concrete texturing mats from the concrete surface. Allow the concrete to set for a minimum of 24 hours.

**Sealing ...** Seal the concrete surface using DECRA-SEAL™ or DECRA-SEAL W/B from W. R. MEADOWS. If there is a concern that the surface may be slippery when wet, use DECK-O-GRIP® or apply SURE-STEP™ from W. R. MEADOWS in the final coat of sealer applied to the concrete surface.

**Cleanup ...** Application equipment should be cleaned promptly after use with mineral spirits or xylene.

### PRECAUTIONS

Use SPECTRUM 910 liquid stamp protectant in an adequately ventilated area. It is recommended that a painter's mask or a personal respirator be worn during the sprayer application. Combustible liquid. Keep away from ignition sources. For exterior use only.

Continued over .....

**W. R. MEADOWS OF CANADA**  
70 Hannant Court, Milton, ON L9T 5C1  
Phone: (905) 878-4122 • Fax: (905) 878-4125  
Montreal Sales: (877) 405-5186

Hampshire, IL / Cartersville, GA / York, PA / Fort Worth, TX  
Benicia, CA / Pomona, CA / Goodyear, AZ / Milton, ON  
St. Albert, AB  
[www.wrmeadows.com](http://www.wrmeadows.com)

## HEALTH AND SAFETY

Avoid contact with skin and eyes. If skin contact occurs, wash affected area immediately with soap and water. Refer to Material Safety Data Sheet for complete health and safety information.

## MASTERFORMAT NUMBER AND TITLE

03 35 33 – Stamped Concrete Finishing

## LEED INFORMATION

May help contribute to LEED credits:

- MR Credit 2: Construction Waste Management
- MR Credit 5: Regional Materials

2014-04-16



© SEALTIGHT is a registered trade mark of W. R. Meadows

**WARRANTY:** W. R. Meadows of Canada warrants that, at the time and place we make shipment, our materials will be of good quality and will conform with our published specifications in force on the date of acceptance of the order. THE FOREGOING WARRANTY SHALL BE EXCLUSIVE AND IN LIEU OF ANY OTHER WARRANTY, EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE AND ALL OTHER WARRANTIES OTHERWISE ARISING BY OPERATION OF LAW, COURSE OF DEALING, CUSTOM OF TRADE OR OTHERWISE. As the exclusive remedy for breach of this Warranty, we will replace defective materials, provided, however, that the buyer examine the materials when received and promptly notify us in writing of any defect before the materials are used or incorporated into a structure. Three (3) months after W. R. Meadows of Canada has shipped the materials, all our Warranty and other duties with respect to the quality of the materials delivered shall conclusively be presumed to have been satisfied, all liability therefore terminates and no action for breach of any such duties may thereafter be commenced. W. R. Meadows of Canada shall in no event be liable for consequential damages. Unless otherwise agreed to in writing, no warranty is made with respect to materials not manufactured by W. R. Meadows of Canada. We cannot warrant or in any way guarantee any particular method of use or application or the performance of materials under any particular condition. Neither this Warranty nor our liability may be extended or amended by our salesmen, distributors or representatives, or by our distributor's representatives, or by any sales information or drawings.