

**PETTIBONE®**


# » CARY-LIFT 304

SPECIFICATIONS



Ruggedly built to perform for the long haul, the Cary-Lift™ 304 offers a number of engineering advantages, including an overhead lift arm design that provides maximum visibility when lifting or moving loads. Featuring robust components like heavy-duty 4-wheel drive axles, the 304 tackles the most demanding material handling jobs time and again.

# SPECIFICATIONS



DIMENSIONS	
1 Overall Height	13' 5" (408 cm) - carrying position 19' 10.5" (606 cm) - max raised position
2 Fork Length	96" (244 cm)
3 Ground Clearance	26" (66 cm)
4 Wheel Base	14' 5" (439 cm)
5 Overall Length	34' 2.5" (1,043 cm) - carrying position 39' 10" (1,214 cm) - at max reach
Overall Width	11' 11" (363 cm)
Total Operating Weight	77,860 lbs (35,317 kg)
ENGINE	
Model/Power	240 HP (179 kW) Cummins® QS8.3
Fuel Tank	95 gal. (360 L)
Fan	Engine driven
Cooling Package	CAC, radiator and transmission
Heating	Engine block heater
HYDRAULICS	
System	Fixed displacement with proportional control
Filter	Hydraulic return oil filtration (10 micron)
Tank	135 gal. (511 L)
Sway Cylinder	5° both right and left of center

PERFORMANCE	
Max Load Capacity (Retracted)	30,000 lbs (13,608 kg) 36" LC from back of fork 60,000 lbs (27,216 kg) tipping load
Max Load Capacity (Extended)	15,000 lbs (6,804 kg) 36" LC from back of fork 20,000 lbs (9,072 kg) tipping load
Maximum Lift Height	14' (427 cm)
Below Grade Reach	4.5" (11.4 cm)
Maximum Reach from Tires	4' 8" (142 cm) retracted 10' 1" (307 cm) extended, forks parallel 8' 10" from ground 9' 4" (284 cm) extended, forks parallel at carrying height
Maximum Travel Speed	3.9 mph (6.3 km/h) 1st gear 7.0 mph (11.3 km/h) 2nd gear 12.5 mph (20.1 km/h) 3rd gear 22.3 mph (35.9 km/h) 4th gear
Turning Radius	25' 5" (775 cm) 4-wheel steer
Transmission	Dana® 6000, 4-speed Powershift; Dana C5000 torque converter
Axles	AxleTech® planetary front & rear; 4-wheel drive
Steering	Hydraulic power steering with 2 wheel, 4 wheel and crab steering
Service Brakes	4-wheel outboard dry hydraulic disc
Parking Brake	Spring applied hydraulic release
Tires	29.5 x 29 3/4 ply interchangeable
Lighting	2 headlights, 2 stop/taillights, 1 reverse light

## FEATURES & OPTIONS

OPERATOR CAB	
Large tinted safety glass windows Rear-view mirror Adjustable suspension seat with seat belt, padded armrests & lumbar support	Tilt/telescopic steering column All-weather cab Dome light
AVAILABLE ATTACHMENTS	
Fork frames Pipe and pole balers Log balers	Scrap balers Tire handlers
OPTIONS	
Rear-view camera with 7" display Air-conditioned cab Additional lift heights	Light packages Additional options available

\* Specifications are subject to change.

**PETTIBONE®**

**PETTIBONE, LLC**  
1100 Superior Avenue  
Baraga, MI 49908  
  
P: 906.379.4529  
info@gopettibone.com  
www.gopettibone.com



<b>1 Year</b>	Full machine and attachment
<b>2 Years</b>	Powertrain and major hydraulic components
<b>3 Years</b>	Machine structure

## WARRANTY