

PL RAIL



PLANERS FOR RAIL TRACKS

PL RAIL

Designed for creating one or two small trenches at sides of rail tracks to be filled later with sound-insulating material. Fitted with two guide wheels positioned at front and rear of milling disks that run on the rail to ensure maximum precision. Wheels available in different shapes and sections for different rail profiles.

WATCH THE VIDEO

Scan the QR code using your smartphone



Hydraulic depth adjustment.

Hydraulic lateral tilt

Hydraulic side shift

Two guide wheels positioned at front and rear of milling disks.

Interchangeable milling disks in different widths and depths, available on request.

Scan the QR code using your smartphone



TECHNICAL DATA

Disk width	A	mm inch
Depth	B	mm inch
Depth adjustment		
Side shift		
Tilt		
Operating weight (1)		kg lbs
Required oil flow		l/min gpm
Maximum oil pressure		BAR psi

PL RAIL

	30 - 40 - 50 - 60 1.2 - 1.6 - 2 - 2.4
	0 - 70 0 - 2.75
	Hydraulic
	1015 2235
	75 - 115 20 - 30
	310 4500

(1) The installer is responsible for ensuring that the equipment meets the prime mover's specifications and weight requirement.
 Simex does not accept responsibility or liability for the information provided. Technical modifications may vary without prior notice.

