

E1-Zoom-IP-Camera-Specification			
	Model	E1 Zoom	
Hardware Features	Image Sensor	1/2.7" CMOS Sensor	
	Display Resolution	2560x1920 (5 Megapixels)	
	Lens	f=2.8-8mm Autofocus, F=1.6, with IR Cut	
	Optical Zoom	3X	
	Angle of View	Horizontal: 48° - 98°	
		Vertical: 37° - 75°	
	Pan/Tilt Angle	Horizontal: 355°	
		Vertical: 50°	
	Auto Tracking	Available	
	Minimum Illumination	0 Lux (with IR Illuminator)	
	IR Distance	12m (40ft) (LED: 10pcs/14mil/850nm)	
	Dimension	Ø80x111mm	
	Weight	250g	
	Power Input	DC 5.0V/1A	
Interface	Power		
	Micro SD Card Slot (Max. 256GB)		
	Built-in Microphone and Speaker		
	Reset Button		
Software Features	Protocols & Standards	HTTPS, SSL, TCP/IP, UDP, HTTP, IPv4, UPnP, RTSP, RTMP, SMTP, NTP, DHCP, DNS, DDNS, FTP, P2P	
	Image Compression	H.264	
	Maximal Frame Rate	20fps	
	Code Rate	1024Kbps ~ 4096Kbps (Default: 4096Kbps)	
	Audio	Two-Way Audio	
	Maximal User Access	20 Users (1 admin account & 19 user accounts); Support up to 12 simultaneous video streams (10 substreams & 2 mainstreams)	
	Browser Supported	Edge, Chrome, Firefox, Safari	
	Smart Alarm	Motion Detection/Person Detection/Pet Detection	
	OS Supported	PC: Windows, Mac OS; Smartphone: iOS, Android	
	Record Mode	Motion Recording; Scheduled Recording; 24/7 Recording	
	Alarm	Siren (customizable)	
Works with	Google Assistant; Reolink Cloud (available in some countries)		
Wireless Features	Wireless Standard	IEEE 802.11a/b/g/n	
	Operating Frequency	2.4/5 GHz	
	Wireless Security	WPA-PSK/WPA2-PSK	
Other Parameters	Temperature	Operating Temperature: -10°C~+55°C	
		Storage Temperature: -40°C~70°C	
	Humidity	Operating Humidity: 20% ~ 85%	
		Storage Humidity: 10% ~ 90%	
Waterproof	No		
Warranty	Limited Warranty	2-year limited warranty. For support, visit https://support.reolink.com/hc/en-us/	