replink

Reolink Go PT Ultra

4K 8MP 4G LTE Wireless Battery/Solar Powered PT Outdoor Camera with Smart Detection & Color Night Vision

- 4K 8MP Ultra HD
- 4G LTE Network
- Color Night Vision

Specifications

Video & Audio		
Image Sensor	1/2.7" CMOS Sensor	
Video Resolution	3840 x 2160 (8 Megapixel)@15fps	
Video Compression	H.265	
Field of View	Fixed Lens, Horizontal: 90°, Vertical: 47° , Diagonal: 110°	
Infrared Night Vision	Up to 10 Meters (33ft) (LED: 2pcs/1.2W/ 850nm)	
Color Night Vision	Spotlight: 2pcs/2.4W/6500K	
Audio	Two-Way Audio	
Alarm		
Smart Alarm	PIR/person/vehicle/animal detection	
PIR Detecting Distance	Adjustable up to 10m (33 ft)	
PIR Detecting Angle	120° Horizontal	
Audio Alert	Customized Audio Alerts	
Recording	Motion-Triggered Recording	

Other AlertsInstant Email Alerts and Push NotificationsPan & Tilt355° Pan, 140° TiltPan & TiltSupports 1 guard position & up to 32 preset positionsPreset PointsSupports 1 guard position & up to 32 preset positionsJC/4C Bandwidth- Europe Version: LTE FDD: B//B3/B7/B8/B20/B28A wCDMA: B//B8 B7/B8/B20/B28A wCDMA: B//B8/B20/B28A wCDMA: B//B5/B8PowerBatterySlattery Battery (Battery Ife varies based on settings, usage & wCDMA: BI/B5/B8SolarReolink Solar Panel 2DC PowerUSB Type-C portLocal StorageMicroSD Card (32GB included, max. 12GCB)Cloud StorageReolink Cloud (only available in some countries)Smart HomeGoogle AssistantWorking Environment-Qperating Temperature-10 to S5° C (14° to 131° F)Weather ResistanceIP64HoresSize & Weight			
Pan &Tilt355° Pan, 140° TiltPreset PointsSupports 1 guard position & up to 32 preset positions <i>JC/4G</i> Bandwidth- Europe Version: LTE FDD: BI/B3/B57/B8/B20/B28A WCDMA: BI/B8 - USA Version: LTE FDD: B2/B4/B5/B12/B13/B14/B66/ B71 - Australia Version: LTE FDD: B2/B4/B5/B12/B13/B14/B66/ B71 - Australia Version: LTE FDD: B1/B3/B5/B12/B13/B14/B66/ B71 - Australia Version: LTE FDD: B1/B3/B5/B7/B8/B28 wCDMA: BI/B5/B8 <i>Power</i> -Battery216Wh Rechargeable Battery (Battery life varies based on settings, usage & temperature)SolarReolink Solar Panel 2DC PowerUSB Type-C portStoragemicroSD Card (32GB included, max. 128GB)Cloud StorageReolink Cloud (only available in some countries)Smart HomeGoogle AssistantWorking Environment-10 to 55° C (14° to 131° F)Weather ResistanceIP64Size & Weight-10 to 55° C (14° to 131° F)	Other Alerts		
Preset Points Supports 1 guard position & up to 32 preset positions SG/4C Bandwidth - Europe Version: LTE FDD: B1/B3/B7/B8/B20/B28A WCDMA: B1/B8 Frequency Bands - Europe Version: LTE FDD: B1/B3/B7/B8/B20/B28A WCDMA: B1/B8 Power - VSA Version: LTE FDD: B1/B3/B5/B7/B8/B28 Power WCDMA: B1/B5/B8 Battery 21.6Wh Rechargeable Battery (Battery life varies based on settings, usage & temperature) Solar Reolink Solar Panel 2 DC Power USB Type-C port Storage microSD Card (32GB included, max. 128GB) Cloud Storage Reolink Cloud (only available in some countries) Smart Home Google Assistant Working Environment -10 to 55° C (14° to 131° F) Weather Resistance IP64	Pan & Tilt		
Preset positions 3G/4C Bandwidth Frequency Bands • Europe Version: LTE FDD: B1/B3/B7/B8/B20/B2BA WCDMA: B1/B3 Frequency Bands • USA Version: LTE FDD: B2/B4/B5/B12/B13/B14/B66/ B71 • USA Version: LTE FDD: B1/B3/B5/B7/B8/B2B Power Battery 21.6Wh Rechargeable Battery (Battery Battery Solar Reolink Solar Panel 2 DC Power USB Type-C port Solar Reolink Solar Panel 2 DC Power USB Type-C port Storage microSD Card (32GB included, max. 128GB) Cloud Storage Reolink Cloud (only available in some countries) Smart Home Google Assistant Working Environment -10 to 55° C (14° to 131° F) Weather Resistance IP64	Pan &Tilt	355° Pan, 140° Tilt	
Frequency Bands· Europe Version: LTE FDD: BI/B3/B7/B8/B20/B28A WCDMA: BI/B3 . USA Version: LTE FDD: B2/B4/B5/B12/B13/B14/B66/ B71 . Australia Version: LTE FDD: B1/B3/B5/B7/B8/B28 WCDMA: B1/B5/B7Power216Wh Rechargeable Battery (Battery life varies based on settings, usage & temperature)Battery21.6Wh Rechargeable Battery (Battery life varies based on settings, usage & temperature)SolarReolink Solar Panel 2DC PowerUSB Type-C portStoragemicroSD Card (32CB included, max. 128CB)Cloud StorageReolink Cloud (only available in some countries)Smart HomeGogle AssistantVorking Environment	Preset Points		
Frequency Bands LTE FDD: B1/B3/B7/B8/B20/B28A WCDMA: B1/B8 · USA Version: LTE FDD: B2/B4/B5/B12/B13/B14/B66/ 	3G/4G Bandwidth		
Battery21.6Wh Rechargeable Battery (Battery life varies based on settings, usage & temperature)SolarReolink Solar Panel 2DC PowerUSB Type-C portStorageMicroSD Card (32CB included, max. 128CB)Local StorageReolink Cloud (only available in some countries)Cloud StorageCoogle AssistantSmart HomeCoogle AssistantVorking Environment-10 to 55° C (14° to 131° F)Weather ResistanceIP64	Frequency Bands	LTE FDD: B1/B3/B7/B8/B20/B28A WCDMA: B1/B8 • USA Version: LTE FDD: B2/B4/B5/B12/B13/B14/B66/ B71 • Australia Version: LTE FDD: B1/B3/B5/B7/B8/B28	
Batterylife varies based on settings, usage & temperature)SolarReolink Solar Panel 2DC PowerUSB Type-C portStorageUSB Type-C portLocal StoragemicroSD Card (32CB included, max. 128CB)Cloud StorageReolink Cloud (only available in some countries)Smart HomeGoogle AssistantSmart Home-10 to 55° C (14° to 131° F)Operating Temperature-10 to 55° C (14° to 131° F)Weather ResistanceIP64	Power		
DC Power USB Type-C port Storage USB Type-C port Local Storage microSD Card (32CB included, max. 128GB) Cloud Storage Reolink Cloud (only available in some countries) Smart Home Google Assistant Smart Home Intersection of the section of the	Battery	life varies based on settings, usage &	
Storage Local Storage microSD Card (32GB included, max. 128GB) Cloud Storage Reolink Cloud (only available in some countries) Smart Home Coogle Assistant Smart Home Coogle Assistant Working Environment -10 to 55° C (14° to 131° F) Weather Resistance IP64	Solar	Reolink Solar Panel 2	
Local StoragemicroSD Card (32GB included, max. 128GB)Cloud StorageReolink Cloud (only available in some countries)Smart HomeGoogle AssistantSmart HomeGoogle AssistantWorking Environment-10 to 55° C (14° to 131° F)Operating Temperature-10 to 55° C (14° to 131° F)Weather ResistanceIP64Size & Weight-10 to 55° C (14° to 131° F)	DC Power	USB Type-C port	
Local storage 128GB) Cloud Storage Reolink Cloud (only available in some countries) Smart Home Coogle Assistant Smart Home Google Assistant Working Environment -10 to 55° C (14° to 131° F) Operating Temperature -10 to 55° C (14° to 131° F) Weather Resistance IP64	Storage		
Cloud storage countries) Smart Home Google Assistant Smart Home Google Assistant Working Environment -10 to 55° C (14° to 131° F) Operating Temperature -10 to 55° C (14° to 131° F) Weather Resistance IP64	Local Storage		
Smart Home Google Assistant Working Environment -10 to 55° C (14° to 131° F) Operating Temperature -10 to 55° C (14° to 131° F) Weather Resistance IP64 Size & Weight	Cloud Storage		
Working Environment Operating Temperature -10 to 55° C (14° to 131° F) Weather Resistance IP64 Size & Weight IP64	Smart Home		
Operating Temperature -10 to 55° C (14° to 131° F) Weather Resistance IP64 Size & Weight IP64	Smart Home	Google Assistant	
Weather Resistance IP64 Size & Weight IP64	Working Environment		
Size & Weight	Operating Temperature	-10 to 55° C (14° to 131° F)	
	Weather Resistance	IP64	
Size Φ 98 x 122mm	Size & Weight		
	Size	Ф 98 x 122mm	

Weight (Battery included)	496g
Warranty	
Limited Warranty	2-year limited warranty. For support, visit https://support.reolink.com/hc/en- us/





Gallery & Specs

- 1. Speaker
- 2. IR LEDs
- 3. Spotlights
- 4. Daylight Sensor
- 5. Lens
- 6. Status LED
- 7. PIR Motion Sensor
- 8. Built-in Microphone
- 1. Antenna
- 2. Battery LED
- 3. USB-C Port
- 4. Power Switch
- 5. Reset Hole
- 6. Nano SIM Card Slot
- 7. microSD Card Slot

www.reolink.com