

Reolink TrackMix Wired LTE

2K Wired 4G LTE Dual-Lens PTZ Camera with 24/7 Recording, Auto Tracking & Auto Zoom.

- Network via 4G LTE or Ethernet Cable
- 24/7 Recording
- Auto Tracking & Auto Zoom
- 2K 4MP Super HD

Specifications

| Video & Audio | |
|--------------------------|---|
| Image Sensor | 1/3"CMOS sensor |
| Video Resolution | Up to: 2560 x 1440 (4.0 megapixels)@15fps |
| Lens | f=2.8mm@F=1.6 , f=8mm@F=1.6 |
| Video Format | H.264,H.265 |
| Field of View | Horizontal: 96°-38° Vertical: 55°-21° |
| Zoom Mode | 6X hybrid zoom |
| Infrared Night Vision | Up to 30 meters (100ft)(LED: 2pcs/850nm) |
| Color Night Vision | Spotlight: 2pcs/4w/6500K/450 Lumens |
| Audio | Two-way audio |
| Power | |
| DC Power | DC 12V/2A |
| Interface | |

| | |
|--------------------------|---|
| Power | DC power port |
| System | Reset button |
| Ethernet | One 10M/100Mbps RJ45 |
| SIM card slot | Nano-SIM |
| SD Card Slot | MicroSD card slot (Max. 256GB) |
| Audio | Built-in microphone and speaker |
| Pan&Tilt | |
| Pan &Tilt | Pan: 355°, Tilt: 0°~90°; (Speed can be set) |
| Auto Tracking | Support |
| Pan & Tilt | |
| Preset | 32 |
| 3G/4G | |
| Frequency Bands | "Europe version: LTE FDD: B1/B3/B7/B8/ B20/B28A WCDMA: B1/B8" "USA version: LTE FDD: B2/B4/B5/B12/B13/ B14/B66/B71" "Australia version: LTE FDD: B1/B3/B5/B7/B8/B28 WCDMA: B1/ B5/B8" |
| Software Features | |
| Maximal Frame Rate | Mainstream: 10fps - 15fps Substream: 10fps - 15fps |
| Code Rate | Mainstream: 1024Kbps -4096Kbps Substream: 64Kbps -672Kbps |
| Browser Supported | "Edge, Chrome, Firefox, Safari Note: This feature is not available when using 4G/3G LTE network." |
| OS Supported | PC: Windows, Mac OS; Smartphone: iOS, Android |
| Smart Alarms | Motion/person/Vehicle/Animal Detection |
| Record Mode | Motion Record/Schedule Record (Default: Motion Record) |

| | |
|----------------------------|--|
| Protocols & Standards | "HTTPS, SSL, TCP/IP, UDP, IPv4, UPnP, RTSP, RTMP, ONVIF, SMTP, NTP, DHCP, DNS, DDNS, FTP, P2P Note: HTTPS, UPnP, RTSP, RTMP, Onvif, DDNS, and FTP are not supported when using 4G/3G LTE network." |
| Maximal User Access | Support up to 12 simultaneous video streams (10 substreams & 2 mainstreams) |
| Work with | Google Assistant, Reolink Cloud |
| Working Environment | |
| Temperature | Operating temperature: -10°C~+55°C (14°F~131°F) |
| Humidity | Operating humidity: 10% ~ 90% |
| Waterproof | IP65 |
| Size & Weight | |
| Dimension | 228*147*129mm |
| Mechanical | |
| Weight (Battery included) | 1.21KG |
| Warranty | |
| Limited Warranty | 2-year limited warranty. For support, visit https://support.reolink.com/hc/en-us/ |

Gallery & Specs



1. Infrared LEDs
2. Network Status LED
3. Lens
4. Microphone
5. Daylight Sensor
6. Spotlights



- 1. microSD Card Slot
- 2. Reset Hole